


Full Colour LCD Signature Pad **signotec DELTA**

**SECURE
UNIQUE
BETTER**

10.1"



MADE IN GERMANY

 Quality • Security • Ecology

Electronic signature capture
greatest security
simple and precise
reliable and durable

signotec
e-signature solutions

signotec DELTA

PRIME SIGN SOLUTIONS



**MADE
IN
GERMANY**
Quality • Security • Ecology

Nothing to hide

The Signature Tablet signotec Delta is designed for applications where it is important to be able to read complete documents before signing them. A4-documents are displayed in their original width. You can comfortably scroll through the document by using the pen. You can start the downward (or upward) document sliding only by brushing the screen with the pen tip. It is the ideal solution for banks, government agencies as well as for companies where complex documents must be read before signing.

A true professional

Unlike other 10-inch devices on the market, the signotec Delta is a true signature pad and not a simple monitor extension. The signotec Delta has the same SDK as all other signotec Signature Pads and is also integrated in all applications. What are the advantages of this? As an integrator and developer, you can fully interact with the pad: Download PDF documents to the pad, create your own graphics, images and texts, create buttons and capture the signature in various formats.

Certificated and safe



With the signotec Delta you are on the safe side, because, thanks to the the associated software „signoSign/2“ (with costs), the pad disposes of outstanding security features. In addition to the image of the signature, also significant characteristics of the signature are going to be saved, therefore abuse is nearly impossible and the evidential value is given. The solution has been certified by

an independent, forensic handwriting examiner. In addition, this system has also been certified by the „TÜV“.

Adaptable

The signotec Delta can be placed on the desk in a space-saving manner or can be brought into an oblique position with its integrated stand. In addition, it comes with a 75 VESA-mounting fixture for mounting on third-party VESA mounts. There are two pen holders for the best ergonomics and the respective application: either horizontally above the device or inclined to the user. The signotec Delta Pad not only proves the groundbreaking quality characteristics of the signotec products. signotec is also taking a new approach in terms of the ability to integrate and, above all, of the security of investment. For the first time, all connection types of the signotec pads are optional available in one device: HID-USB, WIN-USB, virtual COM- Port and Ethernet. You can switch between all operating modes.



HIGHLIGHTS

- 10.1" Colour display (1.280 x 800 Pixel)
- Battery-free pen with 2.048 pressure levels
- Ergonomic pen holder
- Integrated mount
- Optional Ethernet-port

signotec DELTA

Technical Data

Alterations for the technical progress, manufacturing tolerances and mistakes reserved at any time! We reserve the right to alter the technical data without prior notice.

Dimensions

| | |
|-----------|------------|
| Thickness | 13 - 23 mm |
| Width | 280 mm |
| Height | 205 mm |

Display

| | |
|---------------------|--|
| Type | 10.1" full colour TFT with backlight |
| Number of colours | 16,7 Million |
| Resolution | 1.280 x 800 pixel absolute / 150 x 150 ppi |
| Scroll function | Yes, for graphics up to 1.280 x 37.600 pixel |
| Pixell spacing | 0,1695 x 0,1695 mm |
| Surface treatment | 8H Extremely durable, hardened special glass |
| Active signing area | 216,96 mm x 135,6 mm |

Sensor

| | |
|-------------------------|--|
| Resolution | 10.800 x 6.900 pixel / 1.264 x 1.292 dpi |
| Linearity | +/- 0.5 mm (center), +/- 1.0 mm (edge) |
| Technology | ERT (Electronic Resonance Technology), not influence by hand touch |
| Surface hardness | Extremely durable, hardened special glass |
| Pressure stages | 2048 pressure stages |
| Pen | Active and battery-free pen with changeable pen tips |
| Lifespan of the pen tip | 1,2 Mill. at 250 gram pressure and 2,5 cm length |
| Total life | 30 Million signatures |

Electronics/Digitisation

| | |
|------------------------------------|--|
| Output rate of the coordinates | 500 Hz 4D Samples (consisting of x, y, time, pressure) |
| Internal sampling rate | 6.000 samples per second |
| USB port | USB-HID Hi-Speed (high-speed interrupt transfers) and USB Hi-Speed (high-speed bulk transfers) |
| Serial port | Optional via internal virtual serial COM-Port |
| Ethernet port | Optional: 10/100 Mbit/s Ethernet, RJ-45 |
| USB Standby Support | Yes, when relevant signal is present the device will switch off |
| Driver | Not necessary for HID-USB. Only for virtual serial port and WinUSB |
| Software/SDK/Tools | SDK and tools free of charge incl. updates and new versions |
| Data transfer | AES 256 encrypted data transfer between PC and pad via RSA key exchange |
| Serial number | Unique and retrievable internal serial number |
| Firmware | Version is displayed during initialisation and is retrievable via SW |
| Status display | 2 coloured and freely programmable LEDs |
| Power consumption | 950 mA at 4,75 – 5,25 V DC |
| Plug'n'Play | Yes, for both connection types (HID and virtual serial) |
| Readout protection of the firmware | Yes, flash memory is protected against readout |

Miscellaneous

| | |
|--|--|
| Cable port | Micro USB with strain relief to 2x USB-B (Y-cable) |
| Cable length | 2,5 meter |
| Weight | 750 grams |
| Pen attachment | Highly flexible textile tether |
| VESA mount | Size: 75x75mm; Screws: Plastic (Ejot or Schriever), Diameter: 3mm, max. penetration depth: 6,5mm |
| Certifications and standards | TÜV, CE, DIN EN 60950-1, DIN EN 61000-6-1, DIN 61000-6-3 |
| ROHS | ROHS compliant |
| Tamper-proof closure | Optionally the case can be glued |
| Barcode | A barcode with a serial number is located on the device and the cardboard box |
| WEEE-Reg.-Nr. (German register for used devices) | DE 41995888 |

signotec

e-signature solutions



Head Office

signotec GmbH
Am Gierath 20 b
DE-40885 Ratingen
T.: +49 (0) 21 02 - 5 35 75-10
F.: +49 (0) 21 02 - 5 35 75-39

Branch Office North

signotec GmbH
Schützenweg 1 b
DE-31637 Rodewald
T.: +49 (0) 50 74 - 967 27-0
F.: +49 (0) 50 74 - 967 27-69

Office Erfurt

signotec GmbH
Regierungsstr. 28
DE-99084 Erfurt
T.: +49 (0) 21 02 - 5 35 75-36
F.: +49 (0) 21 02 - 5 35 75-39

Mail: info@signotec.de

Web: www.signotec.com

the *better*
choice

